



Technical Data Sheet

3M™ VHB™ Water-Based Promoter UV



[Regulatory Info/SDS](#)

Product Description

3M™ VHB™ Water-Based Promoter UV increases the adhesion of 3M™ VHB™ Tapes to a variety of common medium surface energy (MSE) and high surface energy (HSE) materials. This product was specifically designed for use with 3M™ VHB™ Tapes and accelerates their bond-build rate.

Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Typical Physical Properties

Attribute Name	Value
Color	White
Solids Content by Weight	10.5 %
Flash Point	>65 °C (>150 °F)
Viscosity	≤30 cps (at 23°C)

Handling/Application Information

Surface Preparation

The bonding surface must be clean and dry. Contaminated surfaces should be cleaned with an isopropyl alcohol and water mixture (50/50 or 70/30). A clean lint-free cloth should be used for the cleaning step.

Application Techniques

Shake 3M™ VHB™ Water-Based Promoter UV well before using. Apply a thin, uniform coating to the bonding surface with a lint-free cloth using the minimum amount that will fully coat the surface. Allow 3M™ VHB™ Water-Based Promoter UV to dry thoroughly before applying tape. If applied thinly, 3M™ VHB™ Water-Based Promoter UV dries in 10 minutes or less at room temperature. Be sure that the promoted surface remains free from contaminants prior to applying tape. Porous surfaces may require two applications of 3M™ VHB™ Water-Based Promoter UV for uniform coverage and good adhesion. If two coats are needed, allow the first application of promoter sufficient time to dry before applying the second coat.

Removal Techniques

3M™ VHB™ Water-Based Promoter UV can be removed with isopropyl alcohol or acetone. Vigorous scrubbing may be required. Test in a small, inconspicuous area to ensure that isopropyl alcohol or acetone will not affect the substrate. Carefully read and follow manufacturer's precautions and directions for use when handling cleaning solvents.

Storage and Shelf Life

When stored in the original container at 60-80°F (15-27°C), this product retains its performance and properties for 24 months from the date of manufacture.

- Keep 3M™ VHB™ Water-Based Promoter UV in its original container.
- Transfer only a small amount into a work vessel for use.
- Keep original container tightly sealed to avoid evaporation.

Automotive Disclaimer

Select Automotive Applications:

This product is an industrial product and has not been designed or tested for use in certain automotive applications, such as automotive electric powertrain battery or high voltage applications, which may require the product to be manufactured in a IATF certified facility, meet a Ppk of 1.33 for all properties, undergo an automotive production part approval process (PPAP), or fully adhere to automotive design or quality system requirements (e.g., IATF 16949 or VDA 6.3). Customer assumes all responsibility and risk if customer chooses to use this product in these applications.

Information

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price. Warranty claims must be made within one (1) year from the date of 3M's shipment.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

Disclaimer: 3M industrial and occupational products are intended, labeled, and packaged for sale to trained industrial and occupational customers for workplace use. Unless specifically stated otherwise on the applicable product packaging or literature, these products are not intended, labeled, or packaged for sale to or use by consumers (e.g., for home, personal, primary or secondary school, recreational/sporting, or other uses not described in the applicable product packaging or literature), and must be selected and used in compliance with applicable health and safety regulations and standards (e.g., U.S. OSHA, ANSI), as well as all product literature, user instructions, warnings, and limitations, and the user must take any action required under any recall, field action or other product use notice. Misuse of 3M industrial and occupational products may result in injury, sickness, or death. For help with product selection and use, consult your on-site safety professional, industrial hygienist, or other subject matter expert. For additional product information, visit www.3M.com.

ISO Statement

This product was manufactured under a 3M quality system registered to ISO 9001 standards.

3M™ Industrial Adhesives and Tapes Division
3M Center, St. Paul, MN 55144-1000
3M.com/iatd

3M and Scotch-Weld are trademarks of 3M Company.
©3M 2024 (6/24)